

Specification

- **Application:** Suitable for variety industrial processes, waste water and also food processing.
- **Lens:** Glass standard
- **Material for case:** SS304
- **Material for stem:** SS304
- **Housing enclosure:** IP65
- **Dial size:** Ø 2.5", 4" available
- **Stem diameter:** Ø 6mm, 6.3mm available
- **Max stem length:** 900mm
- **Connection type:** Back, bottom and adjustable angle connection available
- **Thread type:** Standard ½" NPT, ½" BSP available
- **Accuracy:** ±1.0%
- **Operating temperature:** 75% of full scale value
- **Ambient temperature:** -50 °C to 120 °C



Ordering Code

MODEL NO: LSTG -	X	X	X	X	X	X	X	X	X	X	X	X	X
Dial size													
2.5"	2												
4"	4												
Connection													
Back		K											
Bottom		M											
Adjustable		E											
Stem Length													
4"			0	4	0								
6"			0	6	0								
9"			0	9	0								
(Custom range available)													
Stem Diameter													
6.0mm										A			
6.3mm										B			
Material													
Case & stem: SS304										0			
Thread													
½" NPT										N			
½" BSP										B			
Temperature Range													
0-50°C										1	2	5	
0-100°C										1	3	1	
0-200°C										1	3	2	
0-300°C										1	3	3	
-50°C -50°C										0	2	5	
(Custom range available)													
Optional													